

PRIMARY CORNER DESCRIPTION NE Cor. for Section 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 5, 1878, - (DCSO records Vol. 4 Page(s) 79 1653)

-----  
Set Chitemwood post, 4" dia., 4 ft. long, 20" in ground, corner to secs. 26, 27, 34 and 35, from which  
A Maple 16" dia., bears N.75°E., 33 lks. dist.  
A Chitemwood 5" dia., bears S.10°E., 13 lks. dist.  
A Maple 8" dia., bears S.40°W., 48 lks. dist.  
A Maple 7" dia., bears N.60°W., 35 lks. dist.

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1688-89)

-----  
I re-establish corner as follows:  
Set sandstone 12 x 8 x 8 ins., 9" in the ground on hillside sloping S. for NE. corner to sec. 34, marked with 2 notches on the E., and 1 notch on the S. side, from which,  
A Maple 26" dia., bears N.75°W., (Rec. N.75°E) 33 lks. dist. mkd. T22S R9W S27 BT.  
A Maple, stump, 7" dia., bears N.60°W., 35 lks. dist. Marks obliterated.  
The other BTs had been destroyed.  
I Marked:  
A Cedar 50" dia., bears S.4°E., 116 lks. dist. mkd. T22S R9W S35 BT.  
An Alder 6" dia., bears S.37°W., 108 lks. dist. mkd. T22S R9W S34 BT.  
Obliterated the sec. mark on BT in 26 and 27.

Douglas County Surveyors Office - James W. Byron, Surveyor - C.S. File 54/60-35 - Feb. 1968

-----  
Corner searched for, not found.

BLM resurvey by Harvey Wofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCSO records Vol. 40 Page(s) 16042)

-----  
The cor. of secs. 34 and 35 only, determined at record bearing and distance from a bearing tree mkd. by Worrick, in 1894:  
A Cedar 50" dia., bears S.4°E., 116 lks. dist. with illegible scribe marks visible on partially healed blaze.  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION NE Cor. Section 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

and a bearing tree of which I have no record:  
A Fir 33" dia., bears S.50°W., 9 lks. dist., no marks visible on open blaze.

At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 9 W  
        S 27  
    S 34 | S 35  
        1974

from which new bearing trees:  
A Fir 14" dia., bears S.65°E., 67 lks. dist. mkd. T22S R9W S35 BT.  
A Fir 13" dia., bears S.8°E., 146 lks. dist. mkd. T22S R9W S35 BT.  
No suitable tree available within limits in sec. 34.

BLM Corrective Dependent resurvey by Stephen J. Malloy and John P. Farnsworth, Cadastral Surveyors, under Group #'s 1125 and 1226, surveyed Nov./Dec. 1982 - (DCSO records Vol. 47 Page(s) 17913)

-----  
(Corner Report)  
The cor. of secs. 34 and 35, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with 1974 properly mkd. brass cap, from which the remaining original bearing tree:  
A Cedar 50" dia., bears S.4°E., 116 lks. dist. with healed blaze.  
An bearing tree of no record:  
A Fir 36" dia., bears S.50°W., 9 lks. dist. with healed blaze.  
and a bearing tree mkd. by Wofford, etal:  
A Fir 16" dia., bears S.65°E., 67 lks. dist. with healed blaze.