

PRIMARY CORNER DESCRIPTION Sec. cor. for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 4 Page(s) 1634)

Set Fir post 40" long, 5" dia., 16" in ground, for the corner to secs. 14, 15, 22 and 23, from which
A Fir 12" dia., bears N.65°E., 32 lks. dist.
A Fir 10" dia., bears S.84°E., 46 lks. dist.
A Fir 16" dia., bears S.22°W., 100 lks. dist.
A Fir 16" dia., bears N.19°W., 75 lks. dist.

Survey by Wilford N. Haines - For: A. Sagaberd Estates - July 1967 - M 34-31

Found - Orig. BT, N.19°W., down, good scribing.
Orig. BT, N.65°E., now 36", rescribed on bark.
Orig. BT, S.84°E., gone.
Orig. BT, S.19°W., now 48".
Set 5/8" steel rod, from which
Scribed 4" Fir, N.51°W., 23.0 ft.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Jan. 1968 - C.S. File 54/60-28

Found - 5/8" Iron rod at corner.
Orig. 12" now 36" Fir, alive, N.65°E., 21.1 ft., shows scar, rescribed in bark by Haines S14 T22S R9W BT.
Orig. 16" now 40" Fir, alive, S.22°W., 66.0 ft. shows good scar.
Orig. 16" now 24" Fir N.19°W., 49.5 ft., down, scribe visible.
No trace of SE BT.
Haines BT, 4" Fir N.51°W., 23.0 ft., blaze pitched over, scribe visible, Haines button above blaze.
Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 9 W
S 15 | S 14
S 22 | S 23
1968
Reset Iron rod alongside.
New BT - 8" D.Fir S.75°E., 59.8 ft. mkd. T22S R9W S23 CSBT.
This corner lies on very steep, South slope, approx. 180 ft. N. of creek, course W.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. cor. for 14, 15, 22 and 23

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

BLM resurvey by Harvey Wofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCSO records Vol. 40 Page(s) 16039-40)

 The Sec. cor., perpetuated and recorded by Haines, in 1967, monumented with an iron rod, 5/8" dia., firmly set, projecting 4" above ground, subsequently remonumented by Tracy in 1968, with an iron post, 2" dia., lying alongside, with brass cap mkd. County Surveyors Office T22S S14 S15 S22 S23 R9W 1968, from which the remains of the original bearing trees:

A Fir 45" dia., bears N.65°E., 32 lks. dist. with healed blaze.

A Fir 52" dia., bears S.22°W., 100 lks. dist. with healed blaze.

A root hole bears N.19°W., 75 lks. dist. with a down Fir alongside 30" dia., with scribe marks T22S R9W S15 visible on decayed blaze.

and a bearing tree mkd. by Haines:

A Fir 6" dia., bears N.31½°W., 36 lks. dist. with healed blaze.

and a bearing tree mkd. by Tracy:

A Fir 8" dia., bears S.75°E., 91 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron post and iron rod, with brass cap mkd:

T 22 S R 9 W			
S 15	S 14		
S 22	S 23		
1974			

from which a new bearing tree:

A Fir 10" dia., bears N.46½°W., 46 lks. dist. mkd. T22S R9W S15 BT.

Cor. Fd. and used in BLM Corrective Dependent resurvey by Stephen J. Malloy and John P. Farnsworth, Cadastral Surveyors, under Group #'s 1125 and 1226, surveyed Nov./Dec. 1982 - (DCSO records Vol. 47 Page(s) 17912)

Fd. OK, March 1983, by Les Roberts, M 90-52