

PRIMARY CORNER DESCRIPTION Sec. cor. for 2 & 3; 34 & 35, T21-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 895)

-----

Set Hemlock post, 4½ ft. long, 4" sq., 24" in the ground for cor. to secs. 34, 35, 2 and 3, marked T21S S35 on the NE.; R9W S2 on the SE.; T22S S3 on the SW. and S34 on the NW faces with 2 notches on the E. and 4 notches on the W. edges, from which

A Cedar, 7" dia., bears N.53°15'E., 6 lks., mkd: T21S R9W S35 BT.

A Cedar, 30" dia., bears S.80°30'E., 41 lks., mkd: T22S R9W S2 BT.

A Cedar, 26" dia., bears S.53°W., 85 lks., mkd: T22S R9W S3 BT.

A Hemlock, 10" dia., bears N.79°W., 23 lks., mkd: T21S R9W S34 BT.

---

Fd. & used on GLO Resurvey by Elmer O. Worrick, Deputy Surveyor, under contract #632, dated April 28, 1894 (DCSO records Vol. 4 Page(s) 1660-1)

---

Douglas County Surveyors Office - James W. Byron, Surveyor - C.S. File 54/60-18 - Dec. 27, 1967

-----

Corner searched for, not found. Fd. no trace of O.B.Ts. Logged and burned.

---

Dependent resurvey by Boyd W. Peterson & John A. Farmer, Cadastral Surveyors, under Group #1791, surveyed Oct. 1995/Feb. 1998. (DCSO records Vol. 52 Page(s) 19854-5)

-----

At the point for the cor. of secs. 2, 3, 34, and 35 at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T21S	R9W
S34	S35
S3	S2
T22S	
1996	

from which

A fir, 10 ins. diam., bears N.48 3/4°E., 85 lks. dist., mkd. T21S R9W S35 BT.

A fir, 12 ins. diam., bears S.32½°E., 61 lks. dist., mkd. T22S R9W S2 BT.

A fir, 18 ins. diam., bears S.71°W., 47 lks. dist., mkd. T22S R9W S3 BT.

continued next page

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. cor. for 2 & 3; 34 & 35, T21-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 21 ins. diam., bears N. 29½° W., 18 lks. dist., mkd. T21S R9W S34 BT.

Deposit a magnet in a white plastic case at base of stainless steel post.

From this point, a point established as the cor. of secs. 2, 3, 34, and 35, by International Paper Co., now Roseburg Lumber Co., recorded in their office at Reedsport, Oregon, not accepted in this survey due to improper procedures, bears N 4°10'46"E., 0.245 chs. dist., determined at record distance from the remains of bearing trees mkd. by International Paper Co.:

A fir stump, 61 ins. diam., bears S.16½°E., 251 lks. dist., no marks visible.

A cedar stump, 36 ins. diam., bears N.44½°W., 150½ lks. dist., no marks visible.