

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 509200

PRIMARY CORNER DESCRIPTION SW Corner for Sec. 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1689-90)

Set sandstone 14 x 12 x 6 ins., 10" in the ground on hillside sloping E. for the SW. corner of sec. 26, marked with 1 notch on the S. and 2 notches on the E. edges, from which,
A Cedar 16" dia., bears N.57°E., 98 lks. dist. mkd. T22S R9W S26 BT.
A Fir 16" dia., bears N.73°W., 134 lks. dist. mkd. T22S R9W S35 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Feb. 1968 - C.S. File 54/60-34

Found - 16" now 42" Fir stump, N.73°W., 88.4 ft. Open and find scribe.

No trace of other orig. BT or corner stone.
Set Brass cap at cor. mkd: County Surveyors Office

T 22 S R 9 W
| S 26
1968

New BTs -9" Alder N.54°W., 49.6 ft. mkd. T22S R9W S35 CS BT.
6" D.Fir N.14°E., 81.6 ft. mkd. T22S R9W S26 CS BT.
This corner lies 90 ft. E. of rock bluff 25 ft. high on steep NE. slope.