

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 4 Page(s) 1634)

-----  
Set sandstone 16 x 10 x 4, 10" in ground for the ¼ sec. corner, from which  
A Fir 16" dia., bears S.40°E., 8 lks. dist.  
A Fir 60" dia., bears N.80°W., 65 lks. dist.

Survey by Wilford N. Haines - For: A. Sagaberd Estates - July 1967 - M 34-31

-----  
Found - Rock and remains of old BTs.  
Set 5/8" steel rod, from which  
scribed -13" Fir S.34°E., 31.3 ft.  
18" Fir N.55°W., 135.8 ft.

BLM resurvey by Harvey Wofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCSO records Vol. 40 Page(s) 16041)

-----  
The ¼ sec. cor. perpetuated and recorded by Haines in 1967, monumented with the original unmarked sandstone, 16 x 9 x 8 ins., (Rec. 16x10x4 ins.), firmly set, projecting 6" above ground, from which the remains of the original bearing trees:  
A Fir 80" dia., bears S.80°W., 68 lks. dist. with decayed blaze. (Rec. N.80°W. 65 lks.)  
and bearing trees mkd. by Haines:  
A Fir 20" dia., bears N.55°W., 206 lks. dist. with healed blaze.  
A Fir 16" dia., bears S.34°E., 47 lks. dist. with healed blaze.

At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap  
mkd: T 22 S R 9 W

¼  $\frac{S 14}{S 23}$

1974

Deposit corner stone alongside iron post.

Found OK by Quimby, February 1997 - M 124-42

Continued next page...

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Brent Knapp - For: Roseburg Resources - 2/24/2025 - M184-62  
-----  
Found - Brass cap marked "T22S R9W ¼ S14/S23 1974"  
21" D. Fir S.34°E. 31.1' with healed blaze.  
80" Rotted fir stump W.80°W. 44.9'.  
21"x8' capped fir snag N. 55°W. 136.0'.  
New - 13" hemlock N.25°E. 61.0' scribed "S.¼ S.14 BT"  
15" hemlock N.84°E. 28.6' scribed "S.¼ S.14 BT"  
23" alder S.61°W. 3.2' scribed "S.¼ S.23 BT"  
O CRS COORDINATE SYSTEM  
COTTAGE GROVE-CANYONVILLE ZONE