

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 560400

PRIMARY CORNER DESCRIPTION East 1/16 cor. betw secs 14 & 23

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Survey by Wilford N. Haines - For: A. Sagaberd estate - July 1967 - M 34-31

Set 5/8" Steel rod, from which
scribed -28" Fir N.4°W., 86.5 ft.
20" Fir S.19°W., 8.6 ft.

BLM resurvey by Harvey Wofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCS0 records Vol. 40 Page(s) 16040-41)

The E. 1/16 sec. cor., established by Haines in 1967, monumented with an iron pin, 5/8" dia., firmly set, projecting 4" above ground, from which bearing trees mkd. by Haines:

A Fir 30" dia., bears N.4½°W., 131½ lks. dist. with healed blaze.

A Fir 22" dia., bears S.15°W., 13½ lks. dist., with healed blaze.

and bearing trees of which I have no record:

A Fir 30" dia., bears N.52½°W., 64 lks. dist. with healed blaze.

A Fir 34" dia., bears S.56½°W., 42 lks. dist. with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: E 1/16 $\frac{S\ 14}{S\ 23}$

1974

Reset iron pin alongside iron post.

Brent Knapp - For: Roseburg Resources - 2/24/2025 - M184-62

Found - Brass cap marked "E1/16 S14/S23 1974"

30" D. Fir N.4°W. 86.8' with healed scar and tag.

22" D. Fir S.15°W. 8.91' with healed scar and tag.

30" D. Fir N.52°W. 42.2' with healed scar and tag.

34" D. Fir S.56°W. 27.7' with healed scar and tag.

OCCRS COORDINATE SYSTEM

COTTAGE GROVE-CANYONVILLE ZONE