

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 279 survey dated March 5, 1878 (DCSO records Vol. 4 Page(s) 1651)

Set Fir post 4" dia., 40" long, for the corner to secs. 1, 2, 35 and 36, from which

- A Fir 30" dia., bears N.45°E., 10 lks. dist.
- A Fir 30" dia., bears S.40°E., 7 lks. dist.
- A Fir 12" dia., bears S.70°W., 50 lks. dist.
- A Fir 18" dia., bears N.80°W., 36 lks. dist.

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1686-87)

Intersected S. bdy. of T. 11.16 chs. East of corner to secs. 1 and 2, T23S, which I re-established, as follows:

Set Fir post 4½ ft. long, 4" sq., 24" in the ground on hill-side sloping S. for cor. to secs. 1 and 2, T23S, marked T23S 1 on the SE.; R9W S2 on the SW.; with 1 notch on the E. and 5 notches on the West edges, from which

- A Fir 30" dia., bears N.45°E., 10 lks. dist. mkd. T22S R9W S36 BT.
- A Fir 30" dia., bears S.40°E., 7 lks. dist. mkd. T23S R9W S1 BT.
- A Fir 18" dia., bears N.80°W., 36 lks. dist. mkd. T22S R9W S35 BT.
- I marked a Fir 36" dia., bears S.66°W., 270 lks. dist. mkd. T22S R9W S2 BT.

And destroyed marks on BT in secs. 35 and 36.

The desc. of this corner agrees with notes furnished me.

Douglas County Surveyors Office - James W. Byron, Surveyor - C.S. File 54/60-13 - Dec. 13, 1967

Corner searched for, not found. Fd. yellow tag mkd. approx. cor. No BTs.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Feb. 1968 - C.S. File 54/60-32

Found - Orig. BT mkd. in year 1894, 36" now 46" Fir, S.66°W., 178.2 ft. Tree down, chop open and find scribe "T23SR9W".

At point established from above BT, we find probable remains of orig. BTs:

- Burned remains of stump, N.45°E., 6.6 ft.
- Burned remains of stump, S.40°E., 4.6 ft.

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 569100

PRIMARY CORNER DESCRIPTION No. Sec. cor. for 1 & 2 only, T23-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Stump hole N.80°W., 23.8 ft. No scribe at these points.
Measured West from closing corner of secs. 35 and 36, T22S R9W, 732.1 ft., record distance 736.6 ft.
Set Brass cap at cor. mkd:
County Surveyors Office
T 22 S R9W
T 23 S R9W
 1968 S 2 | S 1
New BTs -18" D.Fir S.75°E., 7.5 ft. mkd. T23S R9W S1 CS BT.
 10" D.Fir S.28°W., 19.2 ft. mkd. T23S R9W S2 CS BT
 16" D.Fir West, 9.0 ft. mkd. T23S R9W S2 CS BT.

Cor. Fd. and used in BLM survey by Wofford and Malloy, under Group #1074, surveyed July 1980/Nov. 1982 - (DCSO records, Vol. 43 Pages 16853-54)