

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Corner for Secs. 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1686)

-----  
Set Hemlock post 5 ft. long, 4" sq., 24" in the ground on hillside sloping West for ¼ sec. corner mkd. ¼ S on the W. face, from which,  
    A Fir 20" dia., bears N.85°E., 27 lks. dist. mkd. ¼ S BT  
    A Hemlock 10" dia., bears N.44°W., 43 lks. dist. mkd. ¼ S BT.

Survey by Rockne R. Luckman PLS #1254 - For: International Paper Co - Jan. 13, 1983 - M 93-41

-----  
Set 1½" galv. pipe with brass cap mkd: T22S R9W 1982 W 1/4 35 36 PLS 1254" at proportionate distance, after thorough search.  
Found - A "U.S. Dept. of Int." tag on a 20" Maple bears South, 52.6 ft. Tag states: Approx. 1/4 cor. S35 T22S R9W Date 1-3-45.  
New BTs -13" D.Fir bears N.28°W., 10.9 ft. blazed and scribed on the SW side of tree: W ¼ Sec. 36 T22 R 9.  
    14" D.Fir bears S.63°W., 21.75 ft.: E ¼ S35 T22 R9.

Mark Smalley - For: Roseburg Forest Products - Bill Olson - Ralph McManis - Nov 1998 - C.S. File 65/23-4

-----  
Found - 1982 DCSO BC IP  
    15" D.Fir, N.28°W., 10.9 ft., good, healed, face bears S.40°W., from tree.  
    21" D.Fir, S.63°W., 21.75 ft., good, healed, face bears N.43°E., from tree.  
New BTs- 16" D.Fir, S.15°W., 14.5 ft., "¼ S BT"  
    10" D.Fir, S.75°E., 31.8 ft., "¼ S BT"