

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 600427

PRIMARY CORNER DESCRIPTION M.C. on line between Secs. 13 & 14

Alias _____ Description MC on left bank Umpqua River
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 202 survey dated March 11, 1875 (DCSO records Vol. 4 Page(s) 1630)

Set a meander post, from which,
An Ash, 10" dia., bears S.33°E., 30 lks.
A Willow, 5" dia., bears S.20°W., 9 lks.

BLM dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, and Richard L. Sanford, Surveying Technician, under Group No. 1704, surveyed July 1993 thru June 1995 (DCSO records Vol. 52 Page(s) 19713-14)

Point for the meander cor. of secs. 13 and 14, for the left bank of the Umpqua River, at proportionate distance; there is no remaining evidence of the original corner.
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.

MC
S 14 S 13
T 22 S R 9 W
1993

from which
An alder, 12 ins. diam., bears S. 21¾° E., 63½ lks. dist., mkd. T22S R9W S13 MC BT in the bark.
An alder, 14 ins. diam., bears S. 22½° W., 53 lks. dist., mkd. T22S R9W S14 MC BT in the bark.
Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.