

PRIMARY CORNER DESCRIPTION Sec. cor. for 1, 2, 11 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>Original GLO Survey by W.H. Byars, Deputy Surveyor, under contract # 202, dated March 11, 1875 (DCSO records Vol. 4 Page(s) 1624)</p> <p>-----</p> <p>Set hemlock post, 4 ft long, 5" dia., 18" in ground, for corner to secs. 1, 2, 11, &amp; 12, frm which</p> <p>    A maple, 16" dia., bears N.43°E., 120 lks.          A Fir, 5" dia., bears S.23°E., 65 lks.          A Maple, 24" dia., S.45°W., 15 lks.          A Hemlock, 5" dia., N.62°W., 39 lks.</p>	
<p>GLO Survey by E.O. Worrick, Deputy Surveyor, under contract #632, dated April 28, 1894 (DCSO records Vol. 4 Page(s) 1658)</p> <p>-----</p> <p>Set fir post, 4½ ft. 4" sq. 24" in the ground, mkd: T22S S1 on the NE R9W, S12 on the SE S11 on the SW and S 2 on the NW, faces with 5 notches on the S and 1 notch on the E edges, from which</p> <p>    A fir, 10" dia. bears N.43°E., 182 lks mkd: T22S R9W S1 BT          A fir, 6" dia., bears S.23°E., 55 lks mkd: T22S R9W S12 BT          A maple, 24" dia bears S.40°W. 15 lks mkd: T22S R9W S11 BT          A fir, 10" dia., bears N.65°W., 51 lks mkd: T22S R9W S2 BT</p>	
<p>Douglas County Surveyors Office - James W. Byron, Surveyor - C.S. File 54/60-18 - Dec. 1967</p> <p>-----</p> <p>Corner searched for, not found. Find old tag on 26" Fir stump mkd. "2" on tag. No scribe. No BTs of any kind fd. in area. Logged and burned. Stump is not old enough by ring count.</p>	
<p>Victor McLind - for: Menasha Corp. - Dec. 1996 - M 126-23</p> <p>-----</p> <p>Mon. Set-     1½" Iron Pipe, 30" long, with 2" Brass cap, mkd. "T22S R9W S2 S1 S11 S12 1996 LS 934".</p> <p>Bt's Fd.-     12" Fir, N.45°E., 18.6', scribed "T22S R9W S1 BT"          16" Fir, S.41°E., 33.6', scribed "T22S R9W S12 BT".          10" Fir, S.15°W., 26.2', scribed "T22S R9W S11 BT".          13" Fir, N.22°W., 34.5', scribed "T22S R9W S2 BT"</p> <p>Found -     1½" iron pipe with screw-on cap, no record, bears S.61°34'21"W., 73.14'.</p>	
<p>Fd. Ok by Gary Smithers - Oct 2005 - M148-73</p>	
<p style="text-align: right;">1</p>	