

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1684)

-----  
Set Fir post 4½ ft. long, 4" sq., 24" in ground on hillside sloping E. for ¼ sec. corner, mkd. ¼ S on the N. face, from which  
A Fir 10" dia., bears N.62°E., 57 lks. dist. mkd. ¼ S BT.  
A Fir 36" dia., bears S.77°W., 80 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell and Randy Smith, Crew - Dec. 10, 1982 - C.S. 62/1-32

-----  
Found - Recently set 1½" Iron pipe with brass cap firmly set. Brass cap proportioned by Luckman Surveying in Nov. 1982. (See note on M 93-41 narrative)  
Orig. 10" now 38" Fir with old GLO tag and good scar. I open and find scribed "¼ S 14" deep in the tree. Tree was found alive and well.  
Orig. 36" now 38" Fir, down and rotting. Tree appeared to have fallen on its face so I dug hole under tree and opened to find scribed "¼S"  
Douglas Co. Forest appraisal tag on 21" Hemlock. Tag was dated 4-13-54 and was marked: "Approx 40 ft. N.15°W. to N 1/4 Cor."  
Since the found brass cap did not fit the orig. BTs, I SET a 1" x 30" Iron pipe with brass cap attached at record bearing and distance from the standing orig. 10" now 38" Fir (S.62°W., 37.6 ft.) Bearing and distance to root hole of down 38" Fir BT is: S.72°W., 62.0 ft. (Rec. S.77°W.W., 52.8 ft.) Bearing and distance to found Forest appraisal tag is: S.14°E., 48.0 ft. (Rec. approx. 40 ft. S.15°E.) Found brass cap bears N.13°E., 36.1 ft. from brass cap I set.  
New BTs -21" Hemlock scribed "¼ S36 CS BT" in double blaze, bears S.14°E., 48.0 ft.  
11" Fir scribed "¼ S25 CS BT" in double blaze, bears N.41°W., 12.9 ft.  
Douglas Co. Surveyor Office BT tags placed on all trees.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2149, surveyed Aug. 2006/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21733-4)

-----  
The ¼ sec. cor. of secs. 25 and 36, perpetuated by the Douglas County Surveyor, in 1982; monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.  
from which the remains of the original BTs cont. next pg

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A burned decayed fir stump, 43" dia., bears N.62°E., 37.6 ft., with illegible reverse scribe marks visible on piece replaced in open blaze.

A roothole bears S.77°W., 62.9 ft., with a down decayed fir, 36" dia., alongside, no marks visible. (Record, 52.8 ft.)

and the remains of the bearing trees mkd. by the Douglas County Surveyors Office, in 1982

A decayed hemlock stump, 19" dia., bears S.13¼°E., 47.2 ft., with illegible scribe marks visible on detached blaze.

A roothole bears N.41°W., 13.2 ft., with a down decayed fir, 12" dia., alongside, no marks visible.

and the remains of a bearing tree mkd. by person(s) unknown, reported by Luckman, in 1983

A roothole bears S.88°W., 36.6 ft., with a down decayed fir stump, 14" dia., alongside, no marks visible.

and new bearing trees

A fir, 35" dia., bears N.76¼°E., 46.3 ft., mkd. ¼ S25 BT.

A fir, 5" dia., bears S.71¼°E., 22.0 ft., mkd. X BT.

The geographic position (NAD 1983 (CORS 96)) of the quarter corner of sections 25 and 36, as determined by a direct tie from a GPS observation on a temporary monument processed using the National Geodetic Survey's Online Positioning User Service (OPUS), in 2006, is as follows:

Latitude: 43°37'18.71"N.      Longitude: 123°42'54.60"W.