

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 4 Page(s) 1631)

Set a Post ¼ sec. corner, from which
A Fir 12" dia., bears North, 74 lks. dist.
A Fir 30" dia., bears S.65°E., 9 lks. dist.

BLM remonumentation by James E. Jelley, under Group # 350, surveyed March 6, 1963 - (DCSO records Vol. 33 Page(s) 13662)

The ¼ sec. cor. of secs. 13 and 24, determined at record distance from the original bearing trees:

A sawed Fir stump 28" dia., bears N.2°W., 74 lks. dist., with a healed blaze. (Rec. brg., North)
A Fir 48" dia., bears S.68°E., 9 lks. dist. with a healed blaze. (Rec. brg. S.65°E.)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

¼ $\frac{S\ 13}{S\ 24}$
T 22 S R 9 W
1963

from which a new bearing tree,

A Hemlock 8" dia., bears N.46½°W., 129 lks. dist., mkd. ¼ S13 BT.

Fd. OK, July 1967, by Wilford Haines - M 34-31

Cad. Brass cap & BTs fd OK, DCSO, Dec. 7, 1967 C.S. File 54/60-8

Found OK by R.Quimby, February 1997 - M 124-42

BLM dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, and Richard L. Sanford, Surveying Technician, under Group No. 1704, surveyed July 1993 thru June 1995 (DCSO records Vol. 52 Page(s) 59172)

From the ¼ sec. cor. of secs. 13 and 24, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with properly mkd. brass cap.

from which the remains of original bearing trees

A fir stump, 41 ins. diam., bears N. 2° W., 70 lks. dist., with healed double blaze. (Record, 74 lks.)

A fir, 52 ins. diam., bears S. 68° E., 9 lks. dist., with healed blaze. (Cont. next page)

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Secs. 13 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a bearing tree mkd. by Jelley
A hemlock, 20 ins. diam., bears N. 46½° W., 129 lks.
dist., with healed blaze.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor,
under Group #2149, surveyed Aug. 2006/Oct. 2006 - (DCSO
records Vol. 55 Page(s) 21738-39)

The ¼ sec. cor. of secs. 13 and 24, monumented with an iron
post, 2½" dia., firmly set, projecting 6" above ground, with
brass cap (properly) mkd.
from which an original bearing tree
A fir, 64" dia., bears S.68°E., 5.9 ft., no marks visible.
and a bearing tree mkd. by Jelley in 1963
A hemlock, 26" dia., bears N.46½°W., 85.1 ft., with a
healed blaze.