

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 640434

PRIMARY CORNER DESCRIPTION WC to Special MC in Sec. 13

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, and Richard L. Sanford, Surveying Technician, under Group No. 1704, surveyed July 1993 thru June 1995 (DCSO records Vol. 52 Page(s) 19717)

-----  
Point selected for the witness cor. to the special meander cor. on the N. and S. centerline of sec. 13. (From which the true point for the special meander corner bears N.0°22'00"W., (1.515 chains) 99.99 ft. This point falls in the river where it is impracticable to monument.)

Set a stainless steel post, 28 ins. diam., 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

WC  
SMC  
C  
-----  
S i 13  
C  
1993

from which

An alder, 8 ins. diam., bears S. 33° E., 43½ lks. dist., mkd. X BT in the bark.

A maple, 15 ins. diam., bears S. 48° W., 62 lks. dist., mkd. X BT in the bark.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.