

PRIMARY CORNER DESCRIPTION ¼ cor. to 12 & 13

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original GLO Survey by W.H. Byars, Deputy Surveyor, under contract #202, dated March 11, 1875 (DCSO records Vol. 4 Page(s) 1624)

Cor. Mkd.- W.Oak, 4" Dia.
Bt's - 4" dia. W.Oak, bears North 10 lks.
4" dia. W.Oak, bears S.10°E., 8 lks.

Victor McLind - for: Menasha Corp. - Dec. 1996 - M 126-23

Mon. Fd. - 2½" Iron pipe with ¾" BLM BR. cap mkd. "T22S R9W
¼ S12 S13 1993 B.T.S"
Bt's Fd.- 24" Fir, scribes visible, S.11°W., 36.5'.
21" Fir, scribes visible, N.41°W., 15'.
Note: BLM survey is not yet official I accept this corner pending approval of BLM survey.

Fd. OK - D. Edwards - June 1997 - M 127-17

BLM dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, and Richard L. Sanford, Surveying Technician, under Group No. 1704, surveyed July 1993 thru June 1995 (DCSO records Vol. 52 Page(s) 19715-16)

Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T22S R9W
S 12
1/4
S 13
1993

from which

A fir, 24 ins. diam., bears S. 10½° W., 55½ lks. dist., mkd. 1/4 S13 BT.

A fir, 23 ins. diam., bears N. 41° W., 22½ lks. dist., mkd. 1/4 S12 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.