

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 700174

PRIMARY CORNER DESCRIPTION W. Sec. cor. for 30 & 31 only, T22-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 202 survey dated March 11, 1874 (DCSO records Vol. 4 Page(s) 1595)

-----  
Set Fir post for sec. cor., from which  
A Fir 24" dia., bears N.15°E., 64 lks. dist.  
A Fir 20" dia., bears S.74°E., 128 lks. dist.  
A Fir 36" dia., bears S.84°W., 137 lks. dist.  
A Fir 24" dia., bears N.51°W., 87 lks. dist.

GL0 survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1685)

-----  
Intersected East bdy. (T22-9), 420 lks. North of the cor. to secs. 30 and 31, which is a post, 2 ft. above ground 2" sq. mkd. T22S S30 on the NE.; R8W S31 on the SE.; R9W S36 on the SW.; and S25 on the NW. faces, from which  
A Fir 20" dia., bears N.74°E., 131 lks. dist. mkd. T22S R8W S30 BT.  
A Fir 36" dia., bears S.84°W., 137 lks. dist. mkd. T22S R9W S36 BT.  
A Fir 24" dia. bears N.67°W., 66 lks. dist. mkd. T22S R9W S25 BT.

Agreeing in part with notes furnished by the U.S. Surveyor General.  
The bearing tree in sec. 30 having been killed by fire, I marked:  
A Fir 30" dia., bears N.8°E., 92 lks. dist. mkd. T22S R8W S30 BT.  
I obliterated marks on the bearing trees in sec. 25 and 36.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #436, Surveyed April/May 1960 (DCSO records Vol. 30 Page(s) 12879-80)

-----  
The cor. of secs. 30 and 31 only, determined at record distance from the remaining original bearing trees as described by E.O. Worrick in 1894:  
A Fir 44" dia., bears N.8°E., 92 lks. dist. with a healed blaze.  
A rotted Fir stump, size indeterminate, bears S.77°E., 131 lks. dist. with no marks remaining. (Rec. brg. S.74°E.)  
A rotted Fir stump, size indeterminate, bears S.88°W., 137 lks. dist. with no marks remaining. (Rec. brg. S.84°W.)  
A rotted Fir stump, size indeterminate, bears N.70°W., 66 lks. dist. with no marks remaining. (Rec. brg. N.67°W.)

(Cont. Next Page)

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 700174

PRIMARY CORNER DESCRIPTION W Sec cor for 30 and 31 only, T22-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,  
with brass cap mkd:

T 22 S  
R9W | R8W  
S 36 | S 30  
S 31  
1960

from which new bearing trees

A Fir 8" dia., bears N.31½°E., 64 lks. dist. mkd. T22S R8W  
S30 BT.

A Fir 30" dia., bears S.66½°E., 43 lks. dist. mkd. T22S  
R8W S31 BT.

Fd. and used in BLM survey by Brooks and Peterson, Group #s  
595 & 657, surveyed Aug. 1965/Dec. 1967 (DCSO Records, Vol.  
34 Pages 14105-06)

Fd. and used in BLM survey by Wofford, Group #1005, surveyed  
July/Sept. 1980 (DCSO records, Vol. 43 Page 16781)

Fd. OK, R. Luckman, Jan. 13, 1983, M 93-41

David Edwards - Crew: Brant Miller & Eric Sprinkle - 4/3/2025  
- C.S. File 65/116-001

-----  
Found - Standard BLM brass capped iron pipe from 1962 survey  
in good condition.

Fir stumps N.8°E., 60.7' and N.31½°E., 42.2'

A 44" dia. Fir with healed blaze bears S.66½°E.,  
28.4'

New - A 15" dia. Fir scribed "S30 BT" bears N.20°E.,  
22.4'

A 5.5' steel post is set 2 ft South on line.

Compass decl. 15°E.