

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. cor. for 24 & 25; 19 & 30, T22-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 202 survey dated March 11, 1874 (DCSO records Vol. 4 Page(s) 1632)

Set Fir post 40" long, 4" dia., 20" in ground, for cor. post to secs. 19, 25, 24 and 30, from which

- A Fir 8" dia., bears N.23°E., 8 lks. dist.
- A Fir 6" dia., bears S.76°E., 6 lks. dist.
- A Fir 10" dia., bears S.19°W., 14 lks. dist.
- A Fir 10" dia., bears N.64°W., 41 lks. dist.

BLM survey by Floyd A. Brooks and Peter A. Peterson, Cadastral Surveyors - under Group #'s 595 and 657 - surveyed Aug. 1965/Dec. 1967 - (DCSO records Vol. 34 Page(s) 14107)

Point for the cor., at proportionate distance; the original corner.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 22 S
R 9 W R 8 W
S 24 | S 19
S 25 | S 30
1965

from which

- A Fir 8" dia., bears N.76½°E., 72 lks. dist. mkd. T22S R8W S19 BT.
- A Fir 18" dia., bears S.41°E., 37 lks. dist. mkd. T22S R8W S30 BT.
- A Fir 14" dia., bears S.38°W., 22½ lks. dist. mkd. T22S R9W S25 BT.
- A Fir 16" dia., bears N.19°W., 21 lks. dist. mkd. T22S R9W S24 BT.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2149, surveyed Aug. 2006/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21730)

The cor. of secs. 19, 24, 25, and 30, monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.

from which the remains of the bearing trees mkd. by Brooks and Peterson in 1965-67

- A decayed fir stump, 19" dia., bears N.78¼°E., 47.5 ft., no marks visible. (Record, N.76½°E.)
- A fir stump, 21" dia., bears S.43°E., 24.4 ft., with a healed blaze. (Record, S.41°E.)
- A fir, 16" dia., bears S.38°W., 14.9 ft., with a healed blaze and snow blaze. continued next page

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. cor. for 24 & 25; 19 & 30, T22-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, the westerly of two growing together, 24" dia., bears N.19°W., 13.9 ft., with a healed blaze.
No suitable trees to the E. available.
Corner is located on the W. edge of fir reproduction, edge bears N. and S.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2180 & 2300, surveyed May/Oct. 2007 (DCSO records Vol. 56 Page(s) 22221)

The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., reestablished by Brooks and Peterson in 1965-67; monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Brooks and Peterson

A decayed fir stump, 19" dia., bears N.78¼°E., 47.5 ft., no marks visible.

A fir stump, 21" dia., bears S.43°E., 24.4 ft., with a healed blaze.

A fir, 16" dia., bears S.38°W., 14.9 ft., with a healed blaze and snow blaze.

A fir, the westerly of two growing together, 24" dia., bears N.19°W., 13.9 ft., with a healed blaze.

No suitable bearing trees available to the E.

Corner is located on a SE. slope on the W. edge of fir reproduction, edge bears N. and S.

The geographic position (NAD 1983 (CORS 96)) of the corner of sections 19, 24, 25, and 30, on the west boundary of the township, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS), is as follows:

Latitude: 43°38'10.28"N. Longitude: 123°42'18.39"W.