

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 700420

PRIMARY CORNER DESCRIPTION So. 1/16 cor. for S.13; & S18, T22-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #143, surveyed Oct/Nov. 1931 - (DCSO records Vol. 27 Page(s) 11647)

-----  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for S. 1/16 sec. cor., with brass cap mkd:

S 1/16  
S 13 | S 18  
1931

from which

A Fir 22" dia., bears N.0°45'E., 111 lks. dist. mkd. S 1/16 S18 BT.

A Fir 30" dia., bears S.61°30'W., 45 lks. dist. mkd. S 1/16 S13 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & James Bryon, crew - Aug. 1963 - C.S. File 52/14-76

-----  
Found - Govt. brass cap set in 1931.  
38" Fir N.0°45'E., 73.3 ft., shows good axe scar.  
30" Fir S.61½°W., 29.7 ft. is now down, recent uproot, shows good axe scar.  
New BT - 19" D.Fir N.72°W., 77.0 ft. mkd. S 1/16 S13 CS BT.