

PRIMARY CORNER DESCRIPTION M.C. East bdy. Sec. 13

Alias 878010 Description M.C. left bank, Umpqua River
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1553)

Set meander post on left bank of Umpqua River, from which
A Cottonwood 20" dia., bears N.50°E., 15 lks. dist.
A Maple 4" dia., bears S.86°W., 19 lks. dist.

GLO survey by Geo. F. Rigby, U.S. Cadastral Surveyor, under Group #143, surveyed Oct/Nov. 1931 - (DCSO records Vol. 27 Page(s) 11646 and 11648)

Page 11646:
Left bank of Umpqua River. No trace of the original meander cor. on either side.

Page 11648:
(45.37 Chs.)
Proportionate point for the meander cor. on left bank of Umpqua River, falls on a caving bank where a corner would not last and some distance back from the mean high water line.

(45.56 Chs.) (N.0°55'W.)
Mean high water line on left bank of Umpqua River.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground for witness meander cor. of fracl. secs. 13 and 18, with brass cap mkd:

	M C	
S 13		S 18
R 9 W		R 8 W
T 22		S
	W C	
	1931	

from which
An Alder 9" dia., bears S.40°E., 73 lks. dist. mkd. W C
T22S R8W S18 MC BT.
An Alder 14" dia., bears S.54°W., 76 lks. dist. mkd. W C
T22S R9W S13 M C BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & James Byron, crew - Aug. 1963 - C.S. File 52/14-77

Found - Brass cap set in 1931, now buried 18" below surface of sand.
Dead Alder snag S.54°W., 50.2 ft. Did not look for scribing, snag badly rotted.
Remains of rotted Alder stump S.40°E., 48.2 ft. Too far gone to find markings.
Set 2" Iron pipe alongside brass cap, extends 16" above present level of sand. (Cont. Next Page)

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 700446

PRIMARY CORNER DESCRIPTION M. C. on East bdy. Sec. 13

Alias 878010 Description M.C. on left bank Umpqua River
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New BTs -16" Maple S.42°E., 48.2 ft. mkd. WC MC S18 CS BT.
11" Maple S.63°E., 32.0 ft. mkd. WC MC S18 CS BT.
No trees worth marking West of line.

BLM dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, and Richard L. Sanford, Surveying Technician, under Group No. 1704, surveyed July 1993 thru June 1995 (DCSO records Vol. 52 Page(s) 19711-12)

Point for the meander cor. of secs. 13 and 18, for the left bank of the Umpqua River, at proportionate distance, no monument set. (N.0°49'30"W., 12.54 ft) The witness cor. to the meander cor. of secs. 13 and 18, on the left bank of the Umpqua River, monumented with an iron post, 1 in. diam., firmly set 30 ins. below the surface of the ground, with brass cap mkd.

MC
WC

S 13 | S 18
R 9 W | R 8 W
T 22 S
1931

from which bearing trees by Milo E. Godfrey, Deputy County Surveyor, in 1963,

A maple, 23 ins. diam., bears S. 41½° E., 70½ lks. dist., with healed blaze.

A maple, 15 ins. diam., bears S. 61¼° E., 49 lks. dist., with healed blaze.

No other accessories available.