

PRIMARY CORNER DESCRIPTION Sec cor for 1 & 12; 6 & 7, T22-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 202 survey dated March 11 1874 (DCSO records Vol 4 Page 1588)

-----  
Set a Fir post 44" long, 5" dia. 18" in ground for cor. to secs. 1, 6, 7 and 12, from which

- A Fir 48" dia., bears N.32°E., 24 lks. dist.
- A Fir 20" dia., bears S.64°E., 47 lks. dist.
- A Fir 12" dia., bears S.37°W., 42 lks. dist.
- A Fir 36" dia., bears N.45°W., 6 lks. dist.

GLO resurvey by Elmer O. Worrick, Deputy Surveyor, under Group #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1613) (and pages 1701-02, duplicates of Pg. 1613)

-----  
The Sec. cor. to 1, 12, 6 and 7, which I reestablish as follows:

Set Fir post 4½ ft. long, 4" sq., 24" in the ground, mkd. T22S S6 on the NE.; R8W S7 on the SE.; R9W S12 on the SW.; and S1 on the NW. faces with 5 notches on the S. and 1 notch on the W. edges, from which

- A Fir 48" dia., bears N.32°E., 24 lks. dist. mkd. T22S R8W S6 BT.
- A Fir (stump) 20" dia., bears S.64°E., 47 lks. dist. marks grown over.
- A Fir 12" dia., bears S.42°W., 42 lks. marks grown over.
- A Fir 36" dia., bears N.45°W., 6 lks. dist. mkd. T22S R9W S1 BT.

Practically agreeing with notes furnished me by the U.S. Surveyor General.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Sept. 1963 - C.S. File 52/14-73

- Found - 1" Iron pipe extending 18" above ground surface.  
45" dead Fir N.45°W., 4.0 ft., bark scribing (not orig.) found. "T22S R9W S1". No orig. scribing found, bark badly burned.  
60" dead Fir N.32°E., 15.8 ft., bark scribing, not orig., "T22S R8W S6 BT". No orig. scribing found, bark badly burned, yellow tag dated 4/27/54.  
24" Fir stump S.42°W., 27.7 ft., stump cut low, no marks found.  
No trace of SE BT.  
16" Fir snag, approx. 10 ft. high, scribed in wood "T22S R8W S7", S.77½°E., 35.3 ft., yellow tag dated 4/27/54. (Not orig. BT.)

(Cont. Next Page)

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec cor for 1 & 12; 6 & 7, T22-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

20" Fir stump 5 ft. high, bark scribing "T22S R9W S12 BT", S.65°W., 27.0 ft., yellow tag dated 4/27/54. (Not orig. BT.)  
Set brass cap alongside I.P. mkd: County Surveyors Office  
T 22 S  
R 9 W 

S 1	S 6
S 12	S 7

 R 8 W  
1963  
Rescribe in bark, 45" dead Fir N.40°W., \*N.45°W., 4.0 ft. mkd. T22S R9W S1 CS BT. No live trees available. \*Corrected 3/22/2018  
(No recorded survey found for 1954 information.) (June 1995)

---

Victor McLind - for: Menasha Corp. - Dec. 1996 - M 126-23  
-----  
Found - 1½" iron pipe with 2½" Co. Surveyors's Brass cap mkd. "T22S R9 R8 S1 S6 S12 S7 1963".  
Old BTs- 48" Fir snag, old scar, newer bark scribe, N.45°W., 6.6'.  
46" Fir snag, no scribes, N.38°E., 17.7'  
14" Rotted Fir stump, no scribes, S.41°W., 27.6'  
New BTs- 12" Fir, S.34°E., 15.1', scribed "T22S R8W S7 BT"  
9" Fir, S.32°W., 13.1', scribed "T22S R9W S12 BT"

---

BLM remonumentation by Aaron M Graham, Cadastral Surveyor and Michael Jones Surveying Technician under Group #2199 surveyed April 2008/April 2009 - (DCSO rec Vol 56 Pgs 21937-8)  
-----  
The cor. of secs. 1, 6, 7, and 12, perpetuated by persons unknown, (tags found by Godfrey, dated 4/27/54), subsequently perpetuated by Godfrey in 1963,; monumented with an iron pipe 44" long, 1½" dia., firmly set, projecting 24" above ground, from which the remains of the original bearing trees  
A decayed fir stump, size indeterminate, bears N.40°E., 18.0 ft., no marks visible. (Record, N.32°E, 15.8 ft.)  
A decayed fir stump, size indeterminate, bears N.45°W., 6.6 ft., with illegible scribe marks visible (not original scribe marks). (Record, 4.0 ft.)  
At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 20" in the ground, directly over the iron pipe, with brass cap mkd.  
T 22 S  
R 9 W R 8 W  
S 1 | S 6  
S 12 | S 7  
2008  
from which new bearing trees  
A fir, 16" dia. bears S.72°E., 6.8 ft. mkd. T22S R8W S7 BT  
A fir, 11" dia., bears S.28°E., 29.9 ft., mkd. X BT. CONT.

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec cor for 1 & 12; 6 & 7, T22-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

No other suitable bearing objects available due to recent logging activity.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

from this cor., a point established alongside the cor. by Godfrey, in 1963, but utilized as the cor. by McLind in 1996 bears, N.45°00'00"E., 0.25 ft., monumented with an iron post, 30" long, 1½" dia., firmly set, projecting 16" above ground, with a brass cap mkd. COUNTY SURVEYORS OFFICE T22S R9W R8W S1 S6 S12 S7 1963, and was not utilized for control in this survey due to improper survey procedures, from which bearing trees mkd. by McLind in 1996

A fir, 12" dia., bears S.34°E., 15.1 ft., with a healed blaze.

A fir stump, 9" dia., bears S.32°W., 13.1 ft., with a healed blaze.

Reset this post at same position, 4" below the surface of the ground.