

PRIMARY CORNER DESCRIPTION E. Sec. cor. for 25 & 36 only, T22-11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1892)

-----  
Set a stone 18x12x8 ins., 12" in the ground for cor. to secs. 25, 30, 31 and 36, marked with 5 notches on N. and 1 notch on S. edges, from which,  
An Alder 12" dia., bears N.26°E., 41 lks. dist. mkd. T22S R10W S30 BT.  
A Fir 8" dia., bears S.4°E., 59 lks. dist. mkd. T22S R10W S31 BT.  
A burnt Fir 60" dia., bears S.59°W., 167 lks. dist. mkd. T22S R11W S36 BT.  
An Alder 10" dia., bears N.41°W., 36 lks. dist. mkd. T22S R11W S25 BT.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1784-85)

-----  
Intersect W. bdy. 7.93 chs. N. of cor. to secs. 25, 30, 31 and 36, which is a stone set in the ground 12x8x6 ins., above ground, mkd. with 1 notch on S. and 5 notches on N. faces, from which  
An Alder 2" dia. bears N.26°E., 41 lks. dist. mkd. T22S R10W S30 BT.  
A Fir 8" dia., bears S.4°E., 59 lks. dist. mkd. T22S R10W S31 BT.  
A Fir 60" dia., bears S.59°W., 176 lks. dist. mkd. T22S R11W S36 BT.  
An Alder 10" dia., bears N.41°W., 36 lks. dist. mkd. T22S R11W S25 BT.  
This being out of closing limits, I destroy all marks at this cor. relating to secs. 30 and 31.

Survey by Arnold Gibson - For: Oregon State Board of Forestry - Cook; Redding; Graham; Bodewig, crew - May 30, 1972 - C.S. File 55/233-8

-----  
Original 18x12x18" stone missing.  
Found - 60" burnt Fir bears S.59°W., 167 lks., now 60" snag, in place, scribes "T22S R11W 36" visible.  
10" Alder bears N.41°W., 36 lks., missing, in slide out.  
Set 1½" x 36" galv. iron pipe with 3" bronze cap marked: "OREGON STATE BOARD OF FORESTRY T22S S25 S36 R11W T22S S31 R10W 1971 RS 359", 34 ins. in ground, in mound of rock, and from which, (Cont. Next Page)

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 100172

PRIMARY CORNER DESCRIPTION E. Sec. cor. for 25 & 36 only, T22-11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

19" Fir bears N.41°W., 69.0 ft. to face, scribed  
T22S R11W S25 BT RS 359.  
35" Fir bears West, 100.8 ft. to face, scribed T22S  
R11W S36 BT.  
Set 4"x4"x72" white painted Cedar post 3.0 ft. N.50°W., of  
corner pipe. OSBFD metal location poster on 19" Fir BT,  
N.41°W., 69.0 ft.