

PRIMARY CORNER DESCRIPTION C C for Secs. 30 & 31 only (West side)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1785)

-----  
Set a sandstone 36x20x10 ins., 27" in the ground, marked C C with 1 notch on S. and 5 notches on N. edges, for C.C. to secs. 30 and 31, from which  
A Fir 8" dia., bears N.58°E., 60 lks. dist. mkd. T22S R10W S30 BT.  
A Fir 6" dia., bears S.65°E., 20 lks. dist. mkd. T22S R10W S31 BT.  
A Fir 4" dia., bears N.46°W., 35 lks. dist. mkd. T22S R10W S30 & 31 BT.

Survey by Arnold Gibson - For: Oregon State Board of Forestry Cook; Redding; Graham; Bodewig, crew - May 30, 1972 - C.S. File 55/233-5

-----  
Found - Orig. stone 36" x 20" x 10", in place, CC on W. 5 notches on N. and 2 notches on E., from which,  
8" Fir bears N.58°E., 60 lks.; now 23", in place, face grown over, bearing N.63°E.  
6" Fir bears S.65°E., 20 lks.; now 29" in place, face grown over.  
4" Fir bears N.46°W., 35 lks.; now missing.  
29" Fir, not recorded, bears S.75°W., 10 ft., scribe exposed. Approx. 18 years old by ring count.  
Set 4" x 4" x 72" white painted Cedar post, N.80°E., 2.6 ft. from above stone, from which  
20" Fir bears S.33½°E., 44.9 ft. to face, scribed T22S R10W S31 CC BT.  
23" Fir, orig., bears N.63°E., 40 ft. to face, scribed RS 359.  
OSBFD metal location poster on 29" Fir BT. (orig., S.65°E., 12.3 ft.)

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Feb. 22, 1993 - C.S. File 64/39-13

-----  
Found - Orig. stone, 36" x 20" x 10", laying on side with marks CC on top, 5 notches on N. & + on E. edges  
6" now 29" dia. 7 ft. high burnt D.Fir stump, with a fully healed blaze, bears S.65°E., 13.2 ft. (orig.)  
8" now 26" dia. 4 ft. high burnt D.Fir stump with a fully healed single blaze, bears N.63°E., 40.8 ft. (Rec. N.63°E., 40.0 ft., 1972 OSBF) (Orig)

(Cont. Next Page)

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION C.C. for secs. 30 & 31 only (West side)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

29" dia. 3 ft. high burnt D.Fir stump with a fully healed blaze, bears S.80°W., 10.0 ft. (Rec. OSBFD, S.75°W., 10.0 ft.)

20" dia. 2 ft. high burnt D.Fir stump with evidence of a healed lower blaze, bears S.33½°E., 43.7 ft. to blaze (Rec. S.33½°E., 44.9 ft. possible slope dist., 1972 OSBFD)

No white cedar post from 1972 found.

Set a 2 3/8" dia. brass cap on a 1 3/8" O.D. x 32" long iron pipe at a position determined from bearing trees. BC/IP protrudes 4" above ground. Original stone is placed along southerly edge of BC/IP on top of ground. Brass cap marked:

DOUGLAS COUNTY SURVEYOR

		T	22	S		
R	S	25		S	30	R
1				S	31	1
1				1993		0
W				OFFICE		W

No new accessories.

Orig. stone is placed along southerly edge of BC/IP on top of ground.