

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 18 only (West side)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1804)

-----  
At point of intersection, I Set a post, 4 ft. long, 4" sq., 24" in the ground for closing cor. to secs. 7 and 18 marked C C T22S R10W on E.; S7 on N.; S18 on S. with 2 notches on N. and 4 notches on the S. faces, from which

A Fir 16" dia., bears N.45°E., 60 lks. dist. mkd. T22S R10W S7 BT.

An Alder 5" dia., bears S.60°E., 35 lks. dist. mkd. T22S R10W CC S7 & 18 BT.

An Alder 8" dia., bears S.45°W., 30 lks. dist. mkd. T22S R10W S18 BT.

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy - M. Lenora Ladig; P. Earle; K. Cheney, crew - June 21, 1976 - C.S. File 59/15-21

-----  
Found - An orig. BT, a 16" now 54" D.Fir, in good condition with scribing "S7" visible on previously opened blaze.

We do not find any trace of the remaining orig. BTs or the orig. corner monument.

At the true corner point as determined at the record bearing and distance from the only remaining orig. BT, WE SET a 1" x 30" I.Pipe 26" in the ground, with brass cap attached stamped:

Douglas Co. Surveyor  
T 22 S  
S 13 |  $\frac{S 7}{S 18}$  CC  
R11W                      R10W  
1976

from which,

An orig. BT, a 16" now 54" D.Fir bears N.45°E., 39.6 ft.

New BT, a 12" D.Fir bears S.20°E., 21.5 ft. scribed "CC T22S R10W S18 CS BT" in a double blaze.

The NE corner of sec. 13, T22-11 bears approx. North 50 ft.

Fd. OK. Aug. 1976 by G. Baughman - M 65-12