

PRIMARY CORNER DESCRIPTION E. Sec. cor. for 12 & 13 only, T22-11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1887-88)

I establish the cor. to secs. 7, 12, 13 and 18 in accordance with instructions received from the Surveyor General to run the East bdy. of sec. 12 equal in length to the W. bdy. of the same, which I had already ascertained to be 85.66 chs. I therefore set a post 4 ft. long, 4" sq., 24" in the ground for cor., marked T22S S7 on NE.; R10W S18 on SE.; R11W S13 on SW.; and S12 on NW. faces, with 2 notches on N. and 4 notches on S. edges, from which

A Fir 20" dia., bears N.37°E., 39 lks. dist. mkd. T22S R10W S7 BT.

A Fir 20" dia., bears S.31°E., 30 lks. dist. mkd. T22S R10W S18 BT.

An Alder 4" dia. bears S.58°W., 4 lks. dist. mkd. T22S R11W S13 BT.

An Alder 4" dia., bears N.39°W., 19 lks. dist. mkd. T22S R11W S12 BT.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1804)

I find a post, 4" sq., set firmly 24" above ground, mkd. T22SS7 on NE.; R10W S18 on SE.; R11W S13 on SW.; T22S S12 on NW. faces with 2 notches on the N. and 4 notches on the S. edges, from which

A Fir 20" dia., bears N.37°E., 39 lk.s dist. mkd. T22S R10W S7 BT.

A Fir 20" dia., bears S.31°E., 30 lks. dist. mkd. T22S R10W S18 BT.

An Alder 4" dia., bears S.58°W., 4 lks. dist. mkd. T22S R11W S13 BT.

An Alder 4" dia., bears N.39°W., 19 lks. dist. mkd. T22S R11W S12 BT.

I destroyed all marks at this cor. relating to secs. 7 and 18.

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy - M. Lenora Ladig; P. Earle; K. Cheney, crew - June 21, 1976 - C.S. File 59/15-20

Found - In an area approx. 50 ft. North of C.C. secs. 7 and 18, T22-10, we find:

(Cont. Next Page)

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 100501

PRIMARY CORNER DESCRIPTION E. Sec. cor. for 12 & 13 only, T22-11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A 4" now 14" orig. BT, rotten Alder snag with scar.
Cut into tree. Found no trace of scribing. Bears
S.58°W., 2.6 ft.
A 52" burnt rotten snag, bears South 27.0 ft. This
tree was called as line tree in orig. GLO notes.
Found no trace of the line blaze.
Found no trace of NW BT or orig. corner monument.
At true corner point as determined by the record bearing and
dist. of the orig. SW BT: We set a 1" x 36" I.pipe with
brass cap mkd: Douglas Co. Surveyor
T 22 S
S 12 | S 7
S 13 |
R11W R10W
1976
New BTs -18" D.Fir bears N.61°W., 39.5 ft. scribed "T22S R11W
S12 CS BT" in double blaze.
11" D.Fir bears S.24°W., 44.4 ft. scribed "T22S R11W
S13 CS BT" in double blaze with lower blaze
starting approx. 2 ft. from ground.

Fd. OK, Aug. 1976 by G. Baughman - M 65-12