

PRIMARY CORNER DESCRIPTION M.C. on W. bdy. Sec. 6

Alias 880560 Description M.C. on Left bank of Umpqua River
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 4 Page(s) 1731)

Set the M.P. bet. Tps. 22 S., Rs. 10 and 11, from which
A Willow 5" dia., bears S.35°E., 11 lks. dist.
An Ash 6" dia., bears S.45½°W., 104 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1885)

At the meander cor. to fractional secs. 1 & 6 on the S. bank of the Umpqua River bet. Tps. 22 S., Rs. 10 and 11 W. which is a post, 4" sq. marked M C on N.; R10W S6 on E.; T22S on S.; and R11W S1 on W. faces, from which
An Ash stump 10" dia., bears S.45½°W., 104 lks. dist. mkd. BT Remaining marks cut away.
A Willow stub 7" dia., bears N.35°E., 11 lks. dist., marks obliterated. (rec. S.35°E)
A Spruce 18" dia., bears S.8°E., 169 lks. dist. which I mark T22S R10W MC S6 BT.
A Spruce 30" dia., bears S.14½°W., 134 lks. dist. which I mark T22S R11W S1 MC BT.
Dennis Wagoner's house bears N.85°W. about 6.50 chs. dist.

Homestead Entry Survey No. 213 as surveyed by Ben A. Eddy, Forest Ranger, Under Special Instructions dated Feb. 24, 1917. (DCSO records Vol. 5 Page(s) 1886)

The meander cor. on the range line bet. fractional secs. 6 and 1 T22S R11W, which I reestablish in original position from the original bearing trees.
Set an iron pipe 48" long, 2" dia., 36" in the ground, with nail in wooden plug for chaining point, from which
A Spruce 24" dia., bears S.8°00'E., 169 lks. dist. mkd. T22S R10W MC S6 BT (Orig.)
A Spruce 36" dia., (stump) bears S.16°00'W., 134 lks. dist. mkd. T22S R11W MC S1 BT (Orig.)

Survey by Glenn Baughman - For: P.J. Washburn - Aug. 1976 - M 65-12

Found - 2" Iron pipe with pump bell, from which
48" Spruce bears S.8°E., 111.5 ft. (orig.) Heart rotten, old axe marks visible. Rescribed "S6 MC BT".
(Cont. Next Page)

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 100623

PRIMARY CORNER DESCRIPTION M.C. on W. bdy. Sec. 6

Alias 880560 Description M.C. on Left bank of Umpqua River
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - K. Cheney, crew - Oct. 25, 1976 - C.S. File 59/24-42

Found - A 2" x 30" I.P. with pump bell .3 ft. below ground in marshy area.

A 58" Spruce bears S.8°E., 111.5 ft. with re-scribing by Baughman "S6 MC BT", center rotted, top dead, with creek, course N-NW under tree.

No other orig. trees found.

Set a 1" x 30" I.P. with brass cap 27" in the ground, mkd:
Douglas Co. Surveyor

T 22 S

		M.C.	
R	S 1	S 6	R
11			10
W			W

1976

Cap set in position of found pipe as per bearing and dist. from Fd. BT. Cap set in mound of stone 1½" and 1 ft. below surface of ground. Cap stands .3 ft. above ground. Place I.P. on N. edge of cap. Cor. falls in old N-S fence line. Set sign and post 2 ft. South of cor. 32" above ground. No other BTs available for scribing in West quads.

Douglas Co. Surveyors Office - Randall Smith, Deputy - March 5, 1992 - C.S. File 64/24

Found - 2½" DCSO brass cap on an iron pipe 3" below ground. 18" now 58" dia. broken top Spruce, with a rotted center, partially healed, pitched over blaze, with illegible scribing from M 56-56 visible. BT bears S.8°E., 111.5 ft. (agrees w/rec) orig. BT.

New BT - 9" dia. Alder bark scribed, "MC S1 CS BT" bears S.9½°W., 104.4 ft.

Fd. OK - Jerry Estabrook - Aug. 13, 1996 - M125-60

Found OK by R. Ward, Mar. 2001 - M136-61

FD. Ok by ODOT, M Wagstaff, 12/2019 - ST HWY 38-025A-E