

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 120600

PRIMARY CORNER DESCRIPTION West 1/16 bet. Secs. 6 and 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Glenn Baughman - For: P.J. Washburn - Aug. 1976
(Revised Feb/March 1977) - M 65-12

Set 5/8" Iron rod, from which
 14" Fir bears N.38°W., 16.1 ft. scribed W 1/16 S6 BT.
 14" Fir bears S.61°E., 5.4 ft. scribed W 1/16 S7 BT.
(Note: 1/16 cor. established by Hootman in 1961, bears
S.88°55'21"E, 9.42 ft. and South 1.49 ft.)

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - K.
Cheney, crew - Oct. 25, 1976 - C.S. File 59/24-41

Found - 5/8" I.R. set by Baughman. I.Rod is set in rock
 outcrop on steep West slope.
 14" Fir bears S.61°E., 5.4 ft. Tree blazed and
 scribed "W 1/16."
 14" Fir bears N.38°W., 16.1 ft. Tree blazed and
 scribed "W 1/16 S6 BT."
 A sandstone set by Hootman, bears S.78°E., 9.7 ft.
 Stone mkd. "W 1/16."

Renewal:
 Place DCSO alum. cap on 5/8" Iron rod set by
 Baughman, cap stamped "W 1/16."