

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 31 only

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 4 Page(s) 1744)

-----  
Set a Fir post, 5 ft. long, 5" dia., 20" in ground for the ¼ sec. cor. on S. bdy. of sec. 31, from which  
A Fir 10" dia., bears N.83°E., 126lks. dist.  
A Fir 10" dia., bears S.84°E., 76 lks. dist.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1763)

-----  
Set a post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which  
A Fir 48" dia., bears S.75°E., 110 lks. dist. mkd. ¼ S BT  
An Alder 6" dia., bears S.33°W., 22 lks. dist. mkd. ¼ S BT

GLO survey by Albert N. Gould, Deputy Surveyor, under Contract #762, dated July 12, 1905 - (DCSO records Vol. 5 Page(s) 1975)

-----  
The ¼ sec. cor. on S. bdy. Sec. 31 which is a Fir post, 12" high, firmly set, marked and witnessed as described by the Surveyor General.