

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 141100

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1, (CC T23S Rgs. 10 & 11)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Albert N. Gould, Deputy Surveyor, under Contract #762, dated July 12, 1905 - (DCSO records Vol. 5 Page(s) 1846 C and Pg. 1975)

(Page 1846 C)

Intersect N. bdy. of Tsp. 17 lks. East of the $\frac{1}{4}$ sec. cor. on South bdy. Sec. 31, T22S R10W.

At intersection, I set a sandstone 24"x14"x12" in a mound of stone for closing corner of T23S Rgs. 10 and 11 W., marked CC on S. face with 6 grooves on S., E. and W. edges, from which

An Alder 12" dia., bears S.24°E., 47 lks. dist. mkd. T23S Rg10W S6 BT.

An Alder 12" dia., bears S.40°W., 48 lks. dist., mkd. T23S Rg.11W S1 BT.

(Page 1975)

At the NE cor. of Sec. 1, which is a closing cor. of T23S Rgs. 10 & 11 W. heretofore described. (above)

GLO survey by Levi C. Walker, Deputy Surveyor, under Contract #763, dated June 20, 1905 - (DCSO records Vol. 5 Page 1846 A)

Intersect the NW. cor. of T23S R10W, which is a stone 6x8 ins. firmly set and marked with 6 notches on S. and W. edges, from which

A Fir 10" dia., bears N.50°E., 11 lks. dist. mkd. CC T22S R10W BT.

An Alder 8" dia., bears S.21 $\frac{1}{2}$ °E., 50 lks. dist. mkd. CC T23S R10W S6 BT.

An Alder 10" dia., bears S.47°W., 49 lks. dist. mkd. CC T23S R11W S1 BT.

A Post marked $\frac{1}{4}$ S 1 (S. 31?) bears West 19 lks. dist.