

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1803)

This point falling on a flat rock 30x40 ft. on N. slope, I mark a cross (X) at exact corner point with ¼ S. on W. side for ¼ sec. cor., from which

- A Chittim 4" dia., bears N.28°E., 125 lks. dist. mkd. ¼ S BT.
- A Fir 8" dia., bears S.80°W., 75 lks. dist. mkd. ¼ S BT.

Survey by Lloyd D. Smith - Wit: Tim Van Vleet; Eric Urstadt -For: Oregon Dept. of Forestry - April 25, 1990 - C.S. File 63/114

Found - Cross (X) at exact cor. point with ¼ S on W. side; this point falling on a flat rock, 30' x 40' on North slope, cross (X) and ¼ S missing; sandstone soft and badly decayed. (30'x40' flat rock face in place)

- 4" Chittem bears N.28°E., 125 lks.; now 12" badly decayed Chittem on ground with clump of live Chittem surrounding stump hole.
- 8" Fir bears S.80°W., 75 lks.; now 30" N.78°W., 49.2 ft. exposed scribes ¼. Evidence of BT having moved approx. 3 ft. downhill on a steep rock face. I believe the orig. bearing of S.80°W., should have been N.80°W.

Chiseled 1 ft. x 1 ft. cross (X) at corner point on 30' x 40' rock face, with ¼ on West side.

- New BTs -25" Fir bears N.03°W., 15.6 ft. to an alum. nail in face, scribed ¼ S19 BT.
- 26" Fir bears N.75°E., 33.7 ft. to an alum. nail in face, scribed ¼ S20 BT.
 - 26" Fir bears N.21°E., 34.0 ft. to an alum. nail in face, scribed ¼ S20 BT.
 - 34" Fir bears N.04°W., 29.9 ft. to an alum. nail in face, scribed ¼ S19 BT.

Set 4" x 4" x 72" white painted cedar post N.02°E., 19.2 ft. from corner point.