

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION East 1/4 Cor. for Section 18 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1799)

Marked a bluff 12x30 ft. on S. slope with cross (X) at exact cor. point with $\frac{1}{4}$ S. for $\frac{1}{4}$ sec.cor. from which:

A Fir 4" dia., bears S.18°E., 60 lks. dist. mkd. $\frac{1}{4}$ S BT.

A Fir 4" dia., bears S.48°W., 20 lks. dist. mkd. $\frac{1}{4}$ S BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Dec. 1968 - C.S. File 55/101-2 (see also C.S. 55/101-3 for 1968 report)

Orig. 12'x30' bluff, $\frac{1}{4}$ + S visible at corner point, from which

4" Fir bears S.18°E., 60 lks.; now 25" stump, face closed

4" Fir bears S.48°W., 20 lks.; missing, slide rock.

Set 4" x 4" x 72" white painted cedar post 210 ft. S.30°E., of corner point, from which a:

18" Fir bears S.58°W., 28.5 ft.; scribed $\frac{1}{4}$ S18 BT RS359

9" Fir on spur top, course S.12°W., bears N.82°E., 93.1 ft., scribed $\frac{1}{4}$ S17 BT.

OSBF metal location poster on 18" Fir, S.58°W., 28.5 ft.