

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1798)

-----  
A stone in place 6x4x2 ft. above ground which I marked with cross (X) at exact cor. point with 4 notches on S. and 5 notches on E. for cor. to secs. 7, 8, 17 and 18, from which  
A Fir 8" dia., bears N.89°E., 225 lks. dist. mkd. T22S R10W S8 BT.  
A Fir 8" dia., bears S.85°E., 200 lks. dist. mkd. T22S R10W S17 BT.  
A Fir 40" dia., bears S.44°W., 10 lks. dist. mkd. T22S R10W S18 BT.  
A Fir 4" dia., bears N.26°W., 13 lks. dist. mkd. T22S R10W S7 BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Dec. 23, 1971 - C.S. File 55/233-1

-----  
Original 6'x4'x2' stone, in place, cross (X), 4 notches on S. and 5 notches on the E. sides, from which a:  
8" Fir bears N.89°E., 225 lks.; missing.  
8" Fir bears S.85°E., 200 lks.; missing.  
40" Fir bears S.44°W., 10 lks.; now 40"x14' high stub, scribes R10W visible.  
4" Fir bears N.26°W., 13 lks.; missing.

Rewitnessed:

20" Fir bears N.70°E., 18.6 ft. to face, scribed T22S R10W S8 BT.  
20" Fir bears S.87 3/4°E., 27.3 ft., to face, scribed T22S R10W S17 BT RS359.  
9" Fir bears S.7°W., 21.7 ft., to face, scribed T22S R10W S18 BT.  
22" Fir bears N.19°W., 63.3 ft., to face, scribed T22S R10W S7 BT.

Set 4"x4"x72" white painted Cedar post 4.7 ft. N.36°W. of corner stone. OSFD metal location poster on 20" Fir, N.70°E., 18.6 ft.

Cor. Fd. OK, Aug. 1976 by G. Baughman - M 65-12