

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 5 only, T23-10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 4 Page(s) 1744)

Set an Alder post 5 ft. long, 5" dia., 20" in ground for the cor. to secs. 5 & 6, from which
An Alder 10" dia., bears S.8°E., 47 lks. dist.
A Fir 48" dia., bears S.89°W., 850 lks. dist.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1762)

A Post 4" sq., firmly set 2 ft. above ground for cor. to secs. 5 and 6 marked S5 on E.; T23S R10W on S.; S6 on W.; with 5 notches on E. and 1 notch on W. faces, from which
An Alder 10" dia., bears S.8°E., 47 lks. dist. mkd. T23S R10W S5 BT.
A Fir 48" dia., bears S.89°W., 350 lks. dist. mkd. T23S R10W S6 BT. (In DCSO typed notes, Byar's Fir was record 850 lks.)

GLO survey by Levi C. Walker, Deputy Surveyor, under Contract #763, dated June 20, 1905 - (DCSO records Vol. 5 Page 1846 A)

The cor. of secs. 5 and 6, as set under Contract #292, bears S.88°32'E., 2.69 chs. dist.
I obliterate all trace of this cor. and at the point of intersection, I set a sandstone, 14x12x6 ins., 10" in the ground, for C.C. of secs. 5 and 6, marked CC on S.; with 5 grooves on E., and 1 groove on W. face; from which
A Fir 12" dia., bears S.78°E., 45 lks. dist. mkd. T23S R10W S5 BT.
An Alder 12" dia., bears S.45°W., 9 lks. dist. mkd. T23S R10W S6 BT.
(Point of intersection is 4.94 chs. N.88°41'W. of ¼ sec. cor. Sec. 32, T22S R10W)