

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

(Did not find any "original" notes setting this corner) (V. Laugen, Aug. 1995)

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Nov. 12, 1974 - M 55-13

-----  
1/4 Corner established.  
Set OSBF 1½" galv. I.P. and 3" bronze cap.  
New BTs -21" Willow S.31°E., 17.8 ft. with yellow metal location poster.  
11" Willow S.82°E., 13.3 ft. mkd. with RS 359.  
4" x 4" x 72" white painted cedar post, S.22°E., 3.0 ft.

Fd. OK, DCSO - July 21, 1976 - C.S. File 59/18-6

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 1/14/2009 - C.S. File 67/28-9

-----  
Found - 3" dia., brass cap 9" below surface of ground. Cap slightly westward 1974. Cap marked:

OREGON STATE BOARD OF FORESTRY  
T22S R10W

¼ S 17  
1974

Both willow trees gone (1974 ren)  
5/8" iron rod with 1½" dia., alum cap mkd. "BUNTING A.P.A 8/17 WA OR 7858" bears S.89°47'14"E., 367.38 ft. See M64-62 (1977 monument)

New - 49" dia., cottonwood, double blazed & scribed "¼ S17 CS BT" bears S.33½°E., 149.7 ft.

13" dia., cedar, double blazed & scribed "¼ 17 CS BT" (No "S") bears S.63¼°E., 141.1 ft.

Note - Corner lies on high bank Umpqua River.  
Compass decl. 16¼°E.