

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 256300

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 29 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1786)

-----

A stone in place 6x5 ft., 4 ft. high on W. slope which I mark with cross (X) at exact cor. point with  $\frac{1}{4}$  S. for  $\frac{1}{4}$  sec. cor., from which

A Fir 60" dia., bears N.88°E., 120 lks. dist. mkd.  $\frac{1}{4}$  S BT.

A Cedar 16" dia., bears S.88°E., 100 lks. dist. mkd.  $\frac{1}{4}$  S BT.

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #149, surveyed June 1936. - (DCSO records Vol. 27 Page(s) 11435)

-----

The 1/4 sec. cor. of sec. 29 only is a rock in place, 6 x 5 ft., 4 ft. above ground, mkd. and witnessed as described in the official record. The bearing trees are both dead.

From the cor.,

A Fir 12" dia., bears S.71°00'E., 6 lks. dist. mkd.  $\frac{1}{4}$  S29 BT. (New BT)

A Fir 10" dia., bears S.87°00'E., 28 lks. dist., mkd.  $\frac{1}{4}$  S29 BT. (New BT)

I cut the marks from the old bearing tree which is North of line.