

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. cor. for 32 and 33 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 4 Page(s) 1743)

-----  
Set Fir post 5 ft. long, 5" dia., 20" in ground for the cor. to secs. 32 and 33, from which  
A Fir 6" dia., bears N.13°E., 56 lks. dist.  
A Fir 8" dia., bears N.33°W., 41 lks. dist.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1761)

-----  
(75.50 chs.)  
This sec. cor. to secs. 32 and 33, I also fail to find, it evidently having been destroyed by fire. I therefore made diligent search and at  
(80.00 chs.) (West)  
An Alder 4" dia., on line which I mark for cor. to secs. 33 and 32 marked S33 on E.; T22S R10W on N.; S32 on W.; with four notches on E. and 2 notches on W. faces, from which  
An Alder 4" dia., bears N.75°E., 50 lks. dist. mkd. T22S R10W S33 BT.  
A Fir 40" dia., bears S.35°E., 20 lks. dist. mkd. T22S R10W S32 & 33 BT.  
An Alder 4" dia., bears N.1°W., 17 lks. dist. mkd. T22S R10W S32 BT.