

PRIMARY CORNER DESCRIPTION C C for Secs. 20 and 21 (South)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1796)

-----  
Intersect E. and W. line 16 chs. S.89°51'W. of cor. to secs. 28 and 29, and at point of intersection marked a Fir on line, 8" dia., for cor. to secs. 20 and 21, marked T22S R10W CC on N.; S21 on E.; S20 on W.; with 2 notches on S. and 4 notches on E. faces, from which

- A Fir 8" dia., bears N.40°E., 10 lks. dist. mkd. T22S R10W S21 BT.
- A Fir 4" dia., bears S.18°E., 8 lks. dist. mkd. T22S R10W S20 and 21 CC BT.
- A Fir 6" dia., bears N.15°W., 5 lks. dist. mkd. T22S R10W S20 BT.

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #149, surveyed June 1936. - (DCSO records Vol. 27 Page(s) 11440-41)

-----  
The closing cor. of secs. 20 and 21, which is a Fir tree, 22" dia., with blazes, now completely healed over, on the N, E, and W sides.

Beside the tree  
Set an iron post 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

C C  
T 22 S R 10 W  
S 20 S 21  
S 29  
1936

from which

- A Fir 20" dia., bears N.40°00'E., 12 lks. dist. mkd. T22S R10W S21 CC BT. (Old BT, re-marked on the overgrowth.)
- A Fir 24" dia., bears N.28°00'W., 24 lks. dist. mkd. T22S R10W S20 CC BT. (New BT)
- A Fir 12" dia., bears N.16°00'W., 7 lks. dist. mkd. S R with the rest of the marks burned away. (Old BT)