

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1796-97)

Marked a bluff 6 ft. high, 14 ft. wide with cross (X) at exact cor. point with $\frac{1}{4}$ S. for $\frac{1}{4}$ sec. cor., from which
A Fir 4" dia., bears N.30°E., 28 lks. dist. mkd. $\frac{1}{4}$ S BT.
A Fir 20" dia., bears S.88°W., 26 lks. dist. mkd. $\frac{1}{4}$ S BT

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #149, surveyed June 1936. - (DCSO records Vol. 27 Page(s) 11440)

Proportionate measurement.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd:
 $\frac{1}{4}$
S 20 S 21
1936
from which
A Fir 12" dia., bears N.39°15'E., 24 lks. dist. mkd. $\frac{1}{4}$ S21 BT.
A Fir 10" dia., bears S.51°00'W., 29 lks. dist. mkd. $\frac{1}{4}$ S20 BT.