

PRIMARY CORNER DESCRIPTION NE Sec. cor. for Sec. 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1826-27)

-----  
At a point the cor. to secs. 16 & 17 bears S.0°03'E., I therefore set a sandstone 20x16x8 ins., 16" in the ground for closing cor. to secs. 8 and 17, marked CC with 4 notches on S. and E. edges, from which  
A Fir 28" dia., bears N.10°E., 20 lks. dist. mkd. T22S R10W CC S8 & 17 BT.  
A Fir 20" dia., bears S.31°E., 30 lks. dist. mkd. T22S R10W S17 BT.  
A Fir 36" dia., bears N.89°W., 3 lks. dist. mkd. T22S R10W S8 BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Crew: Cook, Nicholson, Metcalf, Hook - July 20, 1972 - C.S. File 55/233-4

-----  
Original 20" x 16" x 8" sandstone, missing, from which a:  
28" Fir bears N.10°E., 20 lks.; missing.  
20" Fir bears S.31°E., 30 lks.; missing.  
36" Fir bears N.89°W., 3 lks.; missing.  
Ridgetop bears West 2.50 chs.; in place.  
NW corner Sec. 16 bears S.00°03', 1.35 chs.;  
OSBF ppe and cap in place, 1 orig. BT, 1 new BT.  
Set 1½" x 36" galv. iron pipe with 3" bronze cap mkd: "Oregon State Board of Forestry T22S R10W S17 S8 S16 1971 RS 359", 34" in ground, and from which a:  
18" Fir bears N.79°W., 27.4 ft. to face; scribed T22S R10W S17 BT RS 359  
2' high x 8' long rock face bears S.30½°W., 3.5 ft. to face; scribed X BO.  
Set 4" x 4" x 72" white painted cedar post 3.6 ft. S.12°E., of corner pipe.  
OSBF metal location poster on 18" Fir BT, N.79°W., 27.4 ft.