

PRIMARY CORNER DESCRIPTION N. Sec. cor. for 4 & 5 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1752-53)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 4 & 5, marked S4 on E.; T22S R10W S4 & 5 on S.; S5 on W. with 4 notches on E. and 2 notches on W. faces, from which,

- A Fir 40" dia., bears S.10°E., 48 lks. dist. mkd. T22S R10W S4 BT.
- A Fir 4" dia., bears S.7°W., 60 lks. dist. mkd. T22S R10W S5 BT.
- A Cedar 36" dia., bears N.3°W., 44 lks. dist. mkd. T22S R10W S4 & 5 BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1045)

Intersect the point for old cor. of secs. 4 and 5, located by reference to the old bearing trees, which are dead but marked as described by the Surveyor General. At the exact cor. point, Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 4 and 5, with brass cap marked:

S5 | S4
T22S R10W
1919

from which

- A Fir 14" dia., bears S.75°E., 40 lks. dist. mkd. T22S R10W S4 BT.
- An Alder 12" dia., bears S.31°W., 60 lks. dist. mkd. T22S R10W S5 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - May 1968 - C.S. File 54/1-22

Found - 2" I.P. filled with concrete, and brass cap broken off, at corner point with 1919 BTs as follows:
14" now 32" Fir, alive, S.75°E., 26.4 ft., shows good scar. We do not open. Rescribe "T22S R10W S4 CS BT"
12" now 20" Alder, alive, S.31°W., 39.6 ft., shows scar. We rescribe "T22S R10W S5 CS BT".

Set Brass cap at cor. mkd:

(Cont. Next Page)

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION North sec. cor. for 4 and 5 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

County Surveyors Office
T21S
T22S S 5 | S 4 R10W

Deposit old pipe and brass cap alongside.
Used original BTs to rescribe because new trees would be too far.
This cor. lies on steep NW. slope 50 ft. E. of small ravine,
course NE. and approx. 200 ft. W. of top of spur, sloping NE.
Dense salmonberry and vine maple brush.