

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 309500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8 & 9 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1810)

-----

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 8 and 9 mkd. T22S R10W on N.; S9 on E.; S8 on W. with 4 notches on E. and S. faces, from which

A Maple 6" dia., bears N.5°E., 42 lks. dist. mkd. T22S R10W S9 BT.

A Fir 20" dia., bears S.34°W., 66 lks. dist. mkd. T22S R10W S8 & 9 BT.

A Fir 6" dia., bears N.27°W., 63 lks. dist. mkd. T22S R10W S8 BT.

Survey by Ronald Stuntzner - For: Siuslaw National Forest - Sept 1989 - M 108-75

-----

No original evidence found.

Set 2" x 30" alum. pipe with 3" alum. cap mkd. T22S R10W S8 S9 S16 1989 LS 1342.

New BTs -I scribed a 10" D.Fir N.14°E., 7.6 ft. scribed T22S R10W S9 BT.

I scribed a 21" D.Fir N.59°W., 51.6 ft. scribed T22S R10W S8 BT.

Corner falls on North slope 790 ft. West of N-S ridge. (Record 891)