

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 316300

PRIMARY CORNER DESCRIPTION Cor. of Secs. 28 & 29 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1781)

-----

Set stone in place 24x20 ins., 6" above ground which I marked with cross (X) at exact cor. point with 2 notches on S. and 4 notches on E. for cor. to secs. 28 and 29, from which  
A Willow 7" dia., bears S.63°E., 25 lks. dist. mkd. T22S R10W S28 BT.  
A Maple 4" dia., bears S.82°W., 35 lks. dist. mkd. T22S R10W S29 BT.  
A Fir 8" dia., bears N.40°W., 25 lks. dist. mkd. T22S R10W S28 and 29 BT.

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #149, surveyed June 1936. - (DCSO records Vol. 27 Page(s) 11435-36)

-----

The point for cor. of secs. 28 and 29 only, which is recovered from the SE BT. The record gives the cor. point as mkd. on a stone in place, 24x20x6 ins. above ground, but no stone in place was to be found in that vicinity.

At point for cor.

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

S 21  
-----  
S 29 S 28  
T 22 S R 10 W  
1936

from which

A Fir 6" dia., bears S.68°30'E., 35 lks. dist. mkd. T22S R10W S28 BT. (New BT)

The stump of a dead willow 8" dia., bears S.63°00'E., 25 lks. dist. mkd. BT (Old BT)

A Fir 30" dia., bears S.31°00'W., 68 lks. dist. mkd. T22S R10W S29 BT. (New BT)