TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 321400

PRIMARY CORNER DESCRIPTION M C So. bdy. Section 16

Alias 880330 Description M.C. Left bank Umpqua River
Alias Description
Alias Description
Alias Description

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 4 Page(s) 1727)

Marked an Alder 6" dia. for the M.P. bet. secs. 16 and 21.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1836-37)

At 1.35 chs. mouth of Lewder Creek, 50 lks. wide.
A Fir tree 8" dia. which I marked T22S R10W MC on E.; S21 on S.; S16 on N. sides for meander cor. bet. secs. 16 and 21, from which

A Fir 10" dia., bears S.23°W., 5 lks. dist. mkd. T22S R10W S21 MC BT.
A Fir 4" dia., bears N.45°W., 4 lks. dist. mkd. T22S R10W S16 MC BT.

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #149, surveyed June 1936. - (DCSO records Vol. 27 Page(s) 11441-42)

The meander cor. of frac. secs. 16 and 21, which is a Fir tree, 10" dia., blazed on N., S., and E. faces but with no marks visible. Beside the tree cor.,
Set an Iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

T 22 S
S 16\
MC
S 21\
R 10 W
1936

from which

A Fir 11" dia., bears N.45°00'W., 3 lks. dist. with scar of original marks healed over. (Old BT)
A Fir 14" dia., bears N.78°00'E., 9 lks. dist. mkd. T22S R10W S16 MC BT. (New BT)
A Fir 20" dia., bears S.41°30'E., 30 lks. dist. mkd. T22S R10W S21 MC BT. (New BT)
A Fir 12" dia., bears S.73°00'W., 5 lks. dist. with the letters S M just visible at the edge of the overgrowth. (Old BT)