

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #149, surveyed June 1936. - (DCSO records Vol. 27 Page(s) 11442)

Midpoint, and point for $\frac{1}{4}$ sec. cor. falls in river.
At a point S.1°05'E., 5.26 chs. dist. from the point for $\frac{1}{4}$ sec. cor. in the river.

Set an iron post 3 ft. long, 1" dia., 28" in the ground, for witness $\frac{1}{4}$ sec. cor. with brass cap mkd:

W C
 $\frac{1}{4}$ S 16
S 21
1936

from which

A Fir 30" dia., bears S.85°00'E., 116 lks. dist. mkd. WC
 $\frac{1}{4}$ S21 BT.

A Cedar 22" dia., bears S.85°30'W., 61 lks. dist. mkd. WC
 $\frac{1}{4}$ S21 BT.

This witness $\frac{1}{4}$ sec. cor. is on the left bank of the Umpqua River.