

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 353300

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 28 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1781)

A Fir 40" dia., which I marked $\frac{1}{4}$ S. on N. side for $\frac{1}{4}$ sec. cor., from which

A Fir 30" dia., bears N.40°W., 90 lks. dist. mkd. $\frac{1}{4}$ S BT

A Fir 28" dia., bears S.11°E., 50 lks. dist. mkd. $\frac{1}{4}$ S BT

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #149, surveyed June 1936. - (DCSO records Vol. 27 Page(s) 11436)

The $\frac{1}{4}$ sec. cor. of sec. 28 only, which is a Fir tree, 70" di., blazed on N. side but with the marks entirely healed over.

Beside the tree

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

$\frac{1}{4}$ S 28
1936

from which

A Fir 55" dia., bears N.35°00'W., 71 lks. dist. mkd. $\frac{1}{4}$ S BT. I cut the marks from this old bearing tree.

A Fir 12" dia., bears S.44°00'E., 46 lks. dist. mkd. $\frac{1}{4}$ S28 BT. (New BT)

A Maple 10" dia., bears S.76°30'E., 30 lks. dist. mkd. $\frac{1}{4}$ S28 BT. (New BT)