

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 33 and 34 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 4 Page(s) 1742)

-----  
Marked a Fir 8" dia. for the cor. to secs. 33 and 34, from which

- A Fir 9" dia., bears N.2°E., 10 lks. dist.
- A Fir 8" dia., bears N.3°W., 21 lks. dist.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1759)

-----  
(78.00 chs.)

A Fir 12" dia., for cor. to secs. 33 and 34 marked S33 on E.; T22S R10W on N.; S34 on W. with 3 notches on E. and W. faces, from which

- A Fir 9" dia., bears N.2°E., 10 lks. dist. mkd. T22S R10W S33 BT.
- A Fir 8" dia., bears N.3°W., 21 lks. dist. mkd. T22S R10W S34 BT.

I destroy the marks at this cor. and at:  
(80.00 chs. West)

Set a sandstone 20x20x6 ins., 16" in the ground for cor. to secs. 33 and 34 marked with 3 notches on E. and W. faces, from which

- A Fir 40" dia., bears N.42°E., 12 lks. dist. mkd. T22S R10W S33 BT.
- A Fir 8" dia., bears S.55°W., 17 lks. dist. mkd. T22S R10W S33 & 34 BT.
- An Alder 6" dia., bears N.42°W., 14 lks. dist. mkd. T22S R10W S34 BT.

Cor. Fd. and used in GLO survey by Levi Walker in 1906 under Contract #763 (DCSO records, Vol. 7 Page 1847)

Survey by Arnold Gibson with D.L. McConnell, transitman - For: Oregon State Board of Forestry - April 13, 1962 - C.S. File 42/341

-----  
Orig. 20x20x6 in. stone (called 20x6x6 in. by Walker retracement in 1906), found 4" x 11" x 12" stone with 3 notches on side, stone rolled down hill out of place, from which a:

- 40" Fir bears N.42°E., 12 lks.; 40" snag bears N.15°E., 12 lks.
- 8" Fir bears S.55°W., 17 lks.; now 30", face closed.

(Cont. Next Page)

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 33 and 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

6" Alder bears N.42°W., 14 lks.; now missing.  
Also found uprooted 16" tree mkd. originally for cor. 33 & 34 with scribing said to have been obliterated when above corner was set. This tree is 2.14 chs. East of above corner as called for in retracement by L.C. Walker.

Set 1½" x 36" galv. iron pipe with 3" bronze cap mkd. "Ore. St. Bd. of Forestry T22S R10W S33 S34 T23S R10W S4 1962 RS 359", 30" in ground with orig. stone alongside, in mound of stone, and from which a:

22" Fir bears N.62°W., 122.1 ft. scribed T22S R10W S33 BT.

16" Fir bears N.32°E., 17.8 ft. scribed T22S R10W S34 BT RS 359.

OSBF metal location poster on 16" Fir BT.

Set 4" x 4" x 72" white painted cedar post 1.0 ft. SE of corner pipe.