

PRIMARY CORNER DESCRIPTION C C for Secs. 21 and 22 (South)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1793)

-----  
Intersect E. and W. line, 12.50 chs. S.89°57'W. of cor. to secs. 27 and 28. At point of intersection, I Set a sandstone 16x12x10 ins., 12" in the ground for cor. to secs. 21 and 22, marked C C with 2 notches on S. and 3 notches on E. sides, from which

- A Cherry 4" dia., bears N.52°E., 30 lks. dist. mkd. T22S R10W S22 BT.
- A Fir 36" dia., bears South 42 lks. dist. mkd. T22S R10W S21 and 22 BT CC.
- A Cherry 4" dia., bears N.34°W., 40 lks. dist. mkd. T22S R10W S21 BT.

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #149, surveyed June 1936. - (DCSO records Vol. 27 Page(s) 11439)

-----  
The closing cor. of secs. 21 and 22, the point for which is determined from the South bearing tree. The original stone cannot be found and the other two bearing trees, although still to be seen lying on the ground, are too badly decayed for identification.

At point for cor.

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for closing cor. of secs. 21 and 22, with brass cap mkd:

C C  
T 22 S R 10 W  
S 21 S 22  
S 28  
1936

from which

- A Fir 14" dia., bears N.70°30'E., 119 lks. dist. mkd. T22S R10W S22 CC BT (New BT)
- A Fir 10" dia., bears N.36°30'W., 11 lks. dist. mkd. T22S R10W S21 CC BT. (New BT)
- A Fir 60" dia., bears South, 42 lks. dist. mkd. R10W S.  
I destroy the marks on this old bearing tree.

Cor. Fd., 1955/56 by Terry and Coughlin - M 15-17

Closing cor. Fd., GLO P/C and 2 BTs., Dec. 1967 by A. Gibson - M 35-48