

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1793)

A Hemlock 5" dia., which I mark $\frac{1}{4}$ S. on W. side for $\frac{1}{4}$ sec. cor., from which

An Alder 6" dia., bears S.15°W., 30 lks. dist. mkd. $\frac{1}{4}$ S BT
A Fir 6" dia., bears S.20°E., 14 lks. dist. mkd. $\frac{1}{4}$ S BT.

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #149, surveyed June 1936. - (DCSO records Vol. 27 Page(s) 11438)

The $\frac{1}{4}$ sec. cor., which is a Hemlock tree, 8" ins. dia. mkd. $\frac{1}{4}$ S. on West side.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

$\frac{1}{4}$
S 21 S 22
1936

A Fir 24" dia., bears S.80°30'E., 67 lks. dist. mkd. $\frac{1}{4}$ S22 BT. (New BT)

A dead Fir 8" dia., bears S.19°00'E., 12 lks. dist. mkd. $\frac{1}{4}$ S (Old BT)

A Fir 34" dia., bears S.71°00'W., 36 lks. dist. mkd. $\frac{1}{4}$ S21 BT. (New BT)

A dead Alder 8" dia., bears S.13°00'W., 26 lks. dist. with a decayed blaze. (Old BT)

Cor. Fd. Feb. 1955/Apr. 1956 by A.G. Terry and R. Coughlin
M 15-17