

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1824-25)

A stone in place 4x2x2 ft. above ground which I mark with cross (X) at exact cor. point with $\frac{1}{4}$ S. for $\frac{1}{4}$ sec. cor., from which

A Fir 40" dia., bears S.75°E., 50 lks. dist. mkd. $\frac{1}{4}$ S BT.

A Fir 36" dia., bears N.85°W., 20 lks. dist. mkd. $\frac{1}{4}$ S BT.

Survey by Donald L. Peel LS #752 - April 26, 1985 - C.S. File 58/256

Found - 39" x 28" x 18" above ground, stone mkd. "+".
30" rotted and burnt Fir stub, N.77°W., 13.1 ft. to face., scribing visible at eye height " $\frac{1}{4}$ S"

A rotted Fir stub, westerly 2/3 broken off and missing, S.71°E., 33 ft. 35.2 ft. to whats left of tree.

Set at corner point, drilled a hole in the rock and cemented in a 2 $\frac{1}{2}$ " brass cap mkd. "T22S R10W 1/4 S16 S15 PLS 752 1985".
New BTs -19" Fir S.28 $\frac{1}{2}$ °E., 23.2 ft. scribed $\frac{1}{4}$ S15 BT.

22" Fir S.88 $\frac{1}{2}$ °W., 20.2 ft. scribed $\frac{1}{4}$ S16 BT.

Corner lies 30 to 40 ft. East of draw, 1750 ft. more or less northerly up draw. The draw empties into upper end of Housmann's pasture.

Fd. OK, Sept. 1989 by R. Stuntzner - M 108-75