

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION C C for Secs. 15 & 16 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1824)

-----

At a point 6 chs. W. of cor. to secs. 9 and 10, I Set a sandstone 20x16x6 ins., 16" in the ground for cor. to secs. 15 and 16, mkd. C.C. with 3 notches on the E. and 4 notches on the S. edges, from which

A Fir 6" dia., bears N.78°E., 35 lks. dist. mkd. T22S R10W CC S15 & 16 BT.

A Cedar 4" dia., bears S.62°E., 26 lks. dist. mkd. T22S R10W S15 BT.

An Alder 8" dia., bears S.13°W., 50 lks. dist. mkd. T22S R10W S16 BT.

Survey by Ronald Stuntzner - For: Siuslaw National Forest - Sept. 1989 - M 108-75

-----

No evidence of original closing corner found.

Set 2" x 30" alum. pipe with 3" alum. cap mkd. T22S R10W S9 S16 S15 1989 LS 1342.

New BTs -33" Cedar S.29°E., 31.8 ft. scribed T22S R10W S15 CC BT.

20" Cedar S.44°W., 32.2 ft. scribed T22S R10W S16 CC BT.

Corner is on North slope 175 ft. West of a creek. (Rec. 66 ft.)