

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION N. Sec. cor. for 3 & 4 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1751)

Set a sandstone 20x20x10 ins., 15" in the ground for cor. to secs. 3 & 4 marked with 3 notches on E. and 3 notches on W. faces, from which,

An Alder 4" dia., bears N.75°E., 16 lks. dist. mkd. T22S R10W S3 & 4 BT.

An Alder 4" dia., bears S.80°E., 4 lks. dist. mkd. T22S R10W S3 BT.

An Alder 4" dia., bears S.38°W., 14 lks. dist. mkd. T22S R10W S4 BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1043)

Intersect the old cor. of secs. 3 and 4, which is a stone, firmly set, marked and witnessed as described by the Surveyor General. Alongside old stone, Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 3 and 4, with brass cap marked:

S4 S3
T22S R10W
1919

from which

An Alder 8" dia., bears S.80°E., 4 lks. dist. mkd. T22S R10W S3 BT. (Old BT)

An Alder 9" dia., bears S.38°W., 14 lks. dist. mkd. T22S R10W S4 BT. (Old BT)