TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 406500

PRIMARY CORNER DESCRIPTION C C for secs. 9 and 10 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1808-09)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 9 and 10 marked T22S R10W on N.; S10 on E.; S9 on W. with 3 notches on E. and 4 notches on S. faces, from which

A Fir 40" dia., bears N.40°E., 70 lks. dist. mkd. T22S R10W S10 BT.

A Fir 40" dia., bears S.60°W., 90 lks. dist. mkd. T22S R10W S9 and 10 BT.

An Alder 8" dia., bears N.10°W., 40 lks. dist. mkd. T22S R10W S9 BT.

Survey by Burton W. Holt - For: Ted Hutchinson - April 1972 C.S. File 55/249

Found - Old BT, S.60°W., 90 lks. Scribes and tree in good condition.

Old BT, N.60°E., is broken snag and cannot verify. Bearing is correct but distance is 30 lks. too far.

Set Brass cap from the 3 good calls, mkd: T 22 S R 10 W
S 9 S 10
S 15
LS 418
1972

New BTs -43" D.Fir bears N.27°30'W., 13.2 ft. marked T22S R10W S9 BT.

51" D.Fir bears S.26°E., 43.0 ft. marked S15 BT.

I bark scribed both trees and measurements were taken from the face of scribing. Corner is on steep West face 260 ft. West of ridge top.

Fd. OK, Oct. 1989 by R. Stuntzner - M 108-75